

CAT.5E UTP Cable

Product Specifications

Construction & Material :			
Item	Unit	Specification	
Product	-	CAT.5E UTP 4P	
Conductor	Size	AWG	24
	Number	P	4
	Material	-	Solid Bare Copper
	Construction	pcs / mm	1/0.50±0.005
	Diameter	mm	0.500
Insulation	Material	-	HD-PE
	Min.thickness	mm	0.158
	Avg.thickness	mm	0.178
	Diameter	mm	0.91±0.02
	Color	-	Blue×White/Blue Orange×White/Orange Green×White/Green Brown×White/Brown
Twisting	Construction	-	See Cross-Section
Cabling	Construction	-	See Cross-Section
Ripcord	Ripcord	-	1500D Nylon Rope
Jacket	Material	-	PVC
	Min.thickness	mm	0.38
	Avg.thickness	mm	0.49
	Overall Diameter	mm	5.5±0.2
	Color	-	Blue
	Frequency	-	350Mhz
Black Marking	Ink-jet Type	RoHS TYPE CM 60°C (UL) E300968 24AWG CSA LL81295 CMG 60°C FT4 ETL VERIFIED TIA/EIA-568-B.2 CAT.5e ENHANCED UTP 350MHZ GIGABIT READY www.tekdata.com TIA 568B TEKDATA+BATCH NO.+METER MARKING(BY FT)	

Cross - Section View :

